

# NAPO (Model)



## TECHNICAL INFORMATION

[IES Files](#) 

<b>Watt</b>	0.4W – 4W
<b>Luminaire</b>	Up to 225lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	24V
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	White - 11 / Aluminium - 21

## DESCRIPTION

### Construction

- Turned aluminium body.
- Polyester powder paint resistant to UV rays.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- To be operated only with constant voltage 24Vdc Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Opal PMMA screen.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

IP66

IK07

CERTIFIED

### Installation

- Recessed installation.
- Steel spring clips.
- Supplied with recessed installation box made of engineering plastic.
- Supplied with power cord. 22AWG conductors.

## VERSIONS (Click on below link to configure your product)


[trimless](#)

[with trim](#)

### Size:

Ø 1" 31/32  
3" 15/16  
0" 5/8

### Size:

Ø 2" 3/4  
3" 15/16  
0" 25/32

## OPTICS



*See accessories in the next page*

## THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

**1099226X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 0.13 lb